

# Truck Mount Specifications

	<b>Model Specifications and Options</b>	<b>PM040CCP</b>	<b>PM040CG</b>	<b>PM040CM</b>	<b>PM040UCP</b>	<b>PM040UG</b>	<b>PM040UM</b>	<b>PM130CPM</b>	<b>PM130G-DF</b>	<b>PM130G-SF</b>	<b>PM130M</b>	<b>PM200CPM</b>	<b>PM200G-DF</b>	<b>PM200M</b>
Bituminous Oil and Flushing Tanks	Net Liquid Oil Capacity (U.S. Gallons +5% Expansion)	40	40	40	40	40	40	130	130	130	130	200	200	200
	Lockable Fill Opening Diameter (Oil Tank)	4"	4"	4"	4"	4"	4"	10"	10"	10"	10"	10"	10"	10"
	Number of Surge Baffles							1	1	1	1	1	1	1
	Graduated Measuring Stick							STD	STD	STD	STD	STD	STD	STD
	Net Liquid Flushing/Recovery Capacity (U.S. Gallons)	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7	7/7
	Fill Opening Diameter (Flushing/Recovery)Tank	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"	2"/4"
Oil Pumping System	Oil Pumping Capacity (GPM)	13	13	13	13	13	13	13	13	13	13	13	13	13
	Hinged Hood Over Pump/Engine Assembly		STD			STD			STD	STD			STD	
Pump Power Mode	Drive: V-belts with Centrifugal Clutch		1			1			1	1			1	
	160CC Gasoline Engine w/Recoil Start (Z5HR)		STD			STD			STD	STD			STD	
Tank Heating	Recirculating Truck-Engine Coolant w/4 Pass Coils in Oil Tank	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Tank Chassis	Steel Frame Rail Channel Section	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"
Finish	Black Enamel	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
	Yellow (ZYEL) Orange (ZORG) Red (ZRED) White (ZWHT)	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT
Miscellaneous Specifications	Height-unloaded (Top of frame up/Top of frame down)	38"/8"	38"/0	38"/8"	0/26"	0/26"	0/26"	48"/8"	48"/17"	48"/0	48"/8"	53"/8"	53"/17"	53"/8"
	Width	24"	27"	24"	30"	30"	30"	26"	27"	27"	26"	26"	27"	26"
	Length	53"	67"	53"	51"	63"	51"	65"	75"	75"	65"	77"	87"	77"
	Net Weight (Dry) excluding Options (U.S. Pounds)	280	340	265	300	350	285	505	560	560	490	555	610	540
	Installation Instructions	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Miscellaneous Options	Fifty (50) Foot Spray Wand Hose (Z50H)	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT
	160CC Gasoline Engine w/Electric Start (Z5HE)		OPT			OPT			OPT	OPT			OPT	
	115-volt Out-of-Service Tank Heater w/Thermostat (ZETH)	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT
	Spring Rewind Hose Reel w/Hose Guides (ZSRHS)	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT
Key	<b>CP</b> -Clutch Pump <b>M</b> -Hydraulic Motor <b>G</b> -Gas Engine <b>DF</b> -Drop Frame <b>SF</b> -Straight Frame <b>U</b> -Underbody													