

PM060 Specifications

	Model Specifications & Options	
Bituminous Oil Flushing & Recovery Tanks	Net Liquid Oil Capacity (U.S. Gallons +5% Expansion)	60
	Lockable Fill Opening Diameter (Oil Tank)	10"
	Net Liquid Flushing/Recovery Capacity (U.S. Gallons)	7/7
Oil Pumping System	Oil Pumping Capacity (GPM)	13
	Hinged Hood Over Pump/Engine Assembly	Standard
Pump Power Mode	160CC Gasoline Engine with Electric Start	Standard
	Drive: V-belt with Heavy Duty Centrifugal Clutch	Standard
	U-1 Battery	Standard
Tank Heating	Exhaust Heat Bonnet Over Bituminous Pump	Standard
	1½" L.P. Gas Burner	Standard
	3" Diameter Full Length U Shaped Retort Tube	Standard
	0-20 PSI Regulator & Gauge for LPG	Standard
	LPG Safety Out Fire Protection Valve & Thermocouple	Standard
	12 VDC Electric Spark Ignitor	Standard
0-260° F Thermometer	Standard	
Tank Skid	Fork Lift Pockets 4x8 inch Full Length	Standard
	Full 12 Gauge Top	Standard
	Asphalt Flush/Recovery Tanks Bolted to Skid Frame	Standard
	D-rings to Secure Equipment	Standard
Finish	Black Enamel	Standard
	Yellow (ZYEL) Orange (ZORG) Red (ZRED)White (ZWHT)	Option
Miscellaneous Specifications	Height	36"
	Width	37"
	Length	72"
	Net Weight Excluding Options	785#
	Approx. Loaded Weight 60 gal. emulsion, 7 gal. flush & 2 ea. 20# LPG bottles	1,400#
	5 Ft. Light weight Spray Wand with End Shutoff Valve	Standard
	25 Ft. Spray Wand Hose	Standard
Spray Wand Recirculation	Standard	
Miscellaneous Options	Fifty (50) Foot Spray Wand Hose (Z50H)	Option
	D.O.T. Combustible Placards & 20-BC Fire Ext. (ZDOT)	Option
	115-volt Out-of-Service Tank Heater w/Thermostat (ZETH)	Option
	LPG Hand torch w/Regulator, 25 ft. Hose &D-Wraps (ZPJT)	Option