

PM230 Specifications

	Model Specifications and Options	PM230S	PM230SD	PM230T	PM230TD
Bituminous Oil and Flushing Tanks	Net Liquid Oil Capacity (U.S. Gallons +5% Expansion) Lockable Fill Opening Diameter (Oil Tank) Graduated Measuring Stick Net Liquid Flushing/Recovery Capacity (U.S. Gallons) Fill Opening Diameter (Flushing/Recovery) Tank	230 10" Standard 7 2"/na	230 10" Standard 7 2"/na	230 10" Standard 10/13 2"/4"	230 10" Standard 10/13 2"/4"
Oil Pumping System	Oil Pumping Capacity (GPM) Hinged Hood Over Pump/Engine Assembly Hydraulic Drive (ZHYDR) - hood not available	13 Standard Option	26 Standard Option	13 Standard Option	26 Standard Option
Pump Power Mode	Drive: V-belts with Centrifugal Clutch 160CC Gasoline Engine w/Electric Start 240CC Gasoline Engine w/Electric Start U-1 Battery	1 Standard Standard	2 Standard Standard	1 Standard Standard	2 Standard Standard
Tank Heating	Exhaust Heat Bonnet Over Bituminous Pump L. P. Gas Burner w/Retort Tube & Exhaust Stacks 12-volt DC Ignitor	Standard Standard Standard	Standard Standard Standard	Standard Standard Standard	Standard Standard Standard
Distributor Bar Assembly	Distributor Bar Length Valves on 6" Centers w/1½ GPM 80° Spray Nozzles Removable Pair 1-ft. Distributor Bar Extensions (ZDBE)		5' 11 Option		5' 11 Option
Tank Chassis	Operator's Platform w/Expanded Metal Deck & Guard Rail Steel Frame Rail Channel Section Torsion Suspension Axle 3,500 lb. Rated 12-volt Electric Brakes w/Breakaway Switch (ZEBR) Hydraulic Surge Brakes w/Breakaway Switch (ZSBL) 14" Tubeless Tires w/Disc Wheel (2) Formed Steel Fenders w/Non-Skid Safety Steps Top-Wind Folding Tongue Jack (5,000 lb. Capacity) 12-volt Shielded Stop, Turn, Tail and License Lights Lifting Eye (Pair) Adjustable Height Lunette Coupler w/Safety Chains Adjustable Height Clevis Coupler w/Safety Chains (ZCLE) Adj. Height 2 5/16" Ball Coupler w/ Safety Chains (ZBBC) Adjustable Height 2" Ball Coupler w/Safety Chains (ZSBC)	4" Standard	Standard 4" Standard	4" Standard Standard Option Standard Standard Standard Standard Standard	4" Standard Standard Option Standard Standard Standard Standard Standard
Finish	Black Enamel	Standard	Standard	Standard	Standard

	Yellow (ZYEL) Orange (ZORG) Red (ZRED) White (ZWHT)	Option	Option	Option	Option
Miscellaneous Specifications	Height-unloaded	50"	50"	68"	68"
	Width-without Distributor Bar Extensions	40"	40"	63"	66"
	Length-with Standard Lunette Coupler/without *	*92"	*111"	140"	158"
	Wheel Base-Centerline of Coupler to Centerline of Axle			83½"	83½"
	Net Weight (Dry) Excluding Options	785#	990#	1,085#	1,265#
	Gross Vehicle Weight Rating (GWVR)			3,470#	3,470#
Miscellaneous Options	Fifty (50) Foot Spray Wand Hose (Z50H)	Option	Option	Option	Option
	D.O.T. Combustible Placards & 20-BC Fire Ext. (ZDOT)	Option	Option	Option	Option
	115-volt Out-of-Service Tank Heater w/Thermostat (ZETH)	Option	Option	Option	Option
	Spring Rewind Hose Reel w/Hose Guides(1-ZSRHS/2-ZSRHT)	Option 1	Option 1	Option 2	Option 2
	LPG Hand Torch w/Regulator, 25 ft. Hose & D-Wraps (ZPJT)	Option	Option	Option	Option
	Extended Operator's Platform (PM230TPLF)			Option	