

SCM300 Specifications

| MODEL SPECIFICATION & OPTIONS | SCM300 |
|---|---------------|
| Net Liquid Slurry Capacity (U.S. Gallons +10% Expansion) | 300 |
| Fill - Rectangular w/ hinged lid & Inter-splash Guard | 18" x 33 1/4" |
| 3" Camlock Fill with cap | Standard |
| Water Tanks - 19-gallon | 2 |
| Fuel Tank - 19-gallon | 1 |
| Hydraulic Reservoir - 19-gallon | 1 |
| Slurry Gravity Discharge Valve | 4" |
| Mixing Motor - 4 to 1 Reduction to Agitator Shaft | Standard |
| 24 Bhp Gasoline Engine w/Electric Start | Standard |
| 38 Bhp Gasoline Engine w/Electric Start | Option |
| Group 75 Battery | Standard |
| Exhaust Muffler w/ Flex Diverter Pipe | Standard |
| Dual Tire Front Steering Axle 3,070 lb. Rated | Standard |
| Hydraulic Fail Safe Brakes | Standard |
| 20.5 x 8-10 Tire & 9 Gauge Wheel 6 Ply 1535 lb. Load Rated | 4 |
| Fenders 10" x 20" Steel | 2 |
| Hand Rail around Deck | Standard |
| Seat | Standard |
| Raised Expanded Metal Deck | Standard |
| Black Enamel | Standard |
| Yellow (ZYEL) Orange (ZORG) Red (ZRED) White (ZWHT) | Option |
| Height-unloaded | 62" |
| Width-without Squeegees | 63" |
| Width-with Squeegees | 96" |
| Length-With Squeegees | 12' |
| Wheel Base | 74" |
| Net Weight (Dry) Excluding Options (Hydraulic, Fuel & Water Tanks Full) | 3,200# |
| Gross Vehicle Weight Rating (GWVR) (Slurry, Hydraulic, Fuel & Water Tanks Full) | 6,140# |